




Product: RSC 30/9 ☑

7/8" Power Field Attachable Connector: Male, straight, 3-pin(2+PE), black housing, 230 V AC/DC, 12 A


Product Description

7/8" Power Field Attachable Connector: Male, straight, 3-pin(2+PE), black housing, 230 V AC/DC, 12 A

Technical Drawing



Male



Technical Specifications

Technical Data

Product Family: Power Connector Product Sub Family: 7/8" Brand: Lumberg Automation Connector Type: Field Attachable Type of Contact / Gender: male Connector Design: straight Number of Pins: 3 Shielding: Unshielded Attachment Type: Coupling nut with external threads Rated Voltage: 250 V AC/DC Operating Voltage: 230 V AC/DC Rated Current*: 12 A Contact Resistance: > 10 mOhm Insulation Resistance: > 10^9 Ohm Type of Connection: screw terminal Cable Gland: PG 9 Conductor Cross Section: max. 1.5 mm² Ambient Temperature (Operation)*: -40 °C to +90 °C Protection Degree / IP Rating**: IP67 Pollution Degree: 3 acc. to DIN EN 60664-1 (VDE 0110-1)		
Brand: Lumberg Automation Connector Type: Field Attachable Type of Contact / Gender: male Connector Design: straight Number of Pins: 3 Shielding: Unshielded Attachment Type: Coupling nut with external threads Rated Voltage: 250 V AC/DC Operating Voltage: 230 V AC/DC Operating Voltage: 230 V AC/DC Rated Current*: 12 A Contact Resistance: \$ 10 mOhm Insulation Resistance: > 10°9 Ohm Type of Connection: screw terminal Cable Gland: PG 9 Conductor Cross Section: max. 1.5 mm² Ambient Temperature (Operation)*: 40 °C to +90 °C Protection Degree / IP Rating**: IP67	Product Family:	Power Connector
Connector Type: Field Attachable Type of Contact / Gender: male Connector Design: straight Number of Pins: 3 Shielding: Unshielded Attachment Type: Coupling nut with external threads Rated Voltage: 250 V AC/DC Operating Voltage: 230 V AC/DC Rated Current*: 12 A Contact Resistance: ≤ 10 mOhm Insulation Resistance: > 10*9 Ohm Type of Connection: screw terminal Cable Gland: PG 9 Conductor Cross Section: max. 1.5 mm² Ambient Temperature (Operation)*: -40 °C to +90 °C Protection Degree / IP Rating**: 1967	Product Sub Family:	7/8"
Type of Contact / Gender: male Connector Design: straight Number of Pins: 3 Shielding: Unshielded Attachment Type: Coupling nut with external threads Rated Voltage: 250 V AC/DC Operating Voltage: 230 V AC/DC Rated Current*: 12 A Contact Resistance: ≤ 10 mOhm Insulation Resistance: > 10*9 Ohm Type of Connection: screw terminal Cable Gland: PG 9 Conductor Cross Section: max. 1.5 mm² Ambient Temperature (Operation)*: -40 °C to +90 °C Protection Degree / IP Rating**: IF67	Brand:	Lumberg Automation
Connector Design: straight Number of Pins: 3 Shielding: Unshielded Attachment Type: Coupling nut with external threads Rated Voltage: 250 V AC/DC Operating Voltage: 230 V AC/DC Rated Current*: 12 A Contact Resistance: ≤ 10 mOhm Insulation Resistance: > 10^9 Ohm Type of Connection: screw terminal Cable Gland: PG 9 Conductor Cross Section: max. 1.5 mm² Ambient Temperature (Operation)*: -40 °C to +90 °C Protection Degree / IP Rating**: IP67	Connector Type:	Field Attachable
Number of Pins: Shielding: Unshielded Attachment Type: Coupling nut with external threads Rated Voltage: 250 V AC/DC Operating Voltage: 230 V AC/DC Rated Current*: 12 A Contact Resistance: ≤ 10 mOhm Insulation Resistance: > 10*9 Ohm Type of Connection: screw terminal Cable Gland: PG 9 Conductor Cross Section: max. 1.5 mm² Ambient Temperature (Operation)*: -40 °C to +90 °C Protection Degree / IP Rating**:	Type of Contact / Gender:	male
Shielding: Unshielded Attachment Type: Coupling nut with external threads Rated Voltage: 250 V AC/DC Operating Voltage: 230 V AC/DC Rated Current*: 12 A Contact Resistance: ≤ 10 mOhm Insulation Resistance: > 10*9 Ohm Type of Connection: screw terminal Cable Gland: PG 9 Conductor Cross Section: max. 1.5 mm² Ambient Temperature (Operation)*: -40 °C to +90 °C Protection Degree / IP Rating**: IP67	Connector Design:	straight
Attachment Type: Coupling nut with external threads Rated Voltage: 250 V AC/DC Operating Voltage: 230 V AC/DC Rated Current*: 12 A Contact Resistance: ≤ 10 mOhm Insulation Resistance: > 10*9 Ohm Type of Connection: screw terminal Cable Gland: PG 9 Conductor Cross Section: max. 1.5 mm² Ambient Temperature (Operation)*: -40 °C to +90 °C Protection Degree / IP Rating**: 1967	Number of Pins:	3
Rated Voltage: 250 V AC/DC Operating Voltage: 230 V AC/DC Rated Current*: 12 A Contact Resistance: ≤ 10 mOhm Insulation Resistance: > 10*9 Ohm Type of Connection: screw terminal Cable Gland: PG 9 Conductor Cross Section: max. 1.5 mm² Ambient Temperature (Operation)*: -40 °C to +90 °C Protection Degree / IP Rating**: IP67	Shielding:	Unshielded
Operating Voltage: 230 V AC/DC Rated Current*: 12 A Contact Resistance: ≤ 10 mOhm Insulation Resistance: > 10^9 Ohm Type of Connection: screw terminal Cable Gland: PG 9 Conductor Cross Section: max. 1.5 mm² Ambient Temperature (Operation)*: -40 °C to +90 °C Protection Degree / IP Rating**: IP67	Attachment Type:	Coupling nut with external threads
Rated Current*: 12 A Contact Resistance: ≤ 10 mOhm Insulation Resistance: > 10*9 Ohm Type of Connection: screw terminal Cable Gland: PG 9 Conductor Cross Section: max. 1.5 mm² Ambient Temperature (Operation)*: -40 °C to +90 °C Protection Degree / IP Rating**: IP67	Rated Voltage:	250 V AC/DC
Contact Resistance: ≤ 10 mOhm Insulation Resistance: > 10°9 Ohm Type of Connection: screw terminal Cable Gland: PG 9 Conductor Cross Section: max. 1.5 mm² Ambient Temperature (Operation)*: -40 °C to +90 °C Protection Degree / IP Rating**: IP67	Operating Voltage:	230 V AC/DC
Insulation Resistance: > 10^9 Ohm Type of Connection: screw terminal Cable Gland: PG 9 Conductor Cross Section: max. 1.5 mm² Ambient Temperature (Operation)*: -40 °C to +90 °C Protection Degree / IP Rating**: IP67	Rated Current*:	12 A
Type of Connection: screw terminal Cable Gland: PG 9 Conductor Cross Section: max. 1.5 mm² Ambient Temperature (Operation)*: -40 °C to +90 °C Protection Degree / IP Rating**: IP67	Contact Resistance:	≤ 10 mOhm
Cable Gland: PG 9 Conductor Cross Section: max. 1.5 mm² Ambient Temperature (Operation)*: -40 °C to +90 °C Protection Degree / IP Rating**: IP67	Insulation Resistance:	> 10^9 Ohm
Conductor Cross Section: max. 1.5 mm² Ambient Temperature (Operation)*: -40 °C to +90 °C Protection Degree / IP Rating**: IP67	Type of Connection:	screw terminal
Ambient Temperature (Operation)*: -40 °C to +90 °C Protection Degree / IP Rating**: IP67	Cable Gland:	PG 9
Protection Degree / IP Rating**: IP67	Conductor Cross Section:	max. 1.5 mm²
• •	Ambient Temperature (Operation)*:	-40 °C to +90 °C
Pollution Degree: 3 acc. to DIN EN 60664-1 (VDE 0110-1)	Protection Degree / IP Rating**:	IP67
· ,	Pollution Degree:	3 acc. to DIN EN 60664-1 (VDE 0110-1)

Materials

Contact Base Material:	CuZn
Contact Plating:	Cu/Au
Contact Bearer Material:	TPU
Contact Bearer Color:	black
Housing Material:	PA 66
Housing Color:	black
Attachment Material:	Al (anodized) black
O-Ring Material:	NBR

Safety & Environmental Compliance

RoHS Compliant:	yes
-----------------	-----

Notes

Note Derating:	* Notice derating
Protection Degree / IP Rating Note:	** only if mounted and locked in combination with Hirschmann / Lumberg Automation connector.
Note:	Do not connect / disconnect under load.

Variants

Item #	Item Description
11581	RSC 30/9

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.