


PX0801/06 Datasheet

Product Name // Mini Series Inline Cable Connector Body
6mm-8mm Cable (Black Gland)

 [View Product Page](#)



// Product Description:

- Mini Series of modular connectors
- Water and dustproof to IP68 when mated with compatible connector
- Choose type of connector body:
- Part codes prefixed PX0800 - Flex Cable Connectors (mate with PX0801 Inline Cable Connectors, PX08 Mini Series Panel Mount Connectors), optionally choose cable acceptance
- Part codes prefixed PX0801 - Inline Cable Connectors (mate with PX0800 Flex Cable Connectors), optionally choose cable acceptance
- Part codes prefixed PX0802, PX0803, PX0804, PX0805 - Panel Mount Connectors (mate with PX08 Mini Series Flex Cable Connectors)
- Choose type of contacts from Screw Terminal, Solder/Crimp Contacts, BNC
- Choose number of connector Contacts and select appropriate connector insert/contact carrier:

- Screw Terminal inserts available separately in 2, 3, 4, 6 Contact, Pin or Socket
- Solder, Crimp Contact carriers available separately in 3, 8 Contact; select appropriate Contact Pins or Sockets and Polarising/Blanking Pins, Contact Insertion Tool, Crimping Tool as required (all available separately)
- BNC Plug or Socket insert available separately in 50 Ohm, 75 Ohm versions for all connector body styles except PX0803
- PX0800, PX0801 Flex and Inline Cable Connector bodies have a choice of cable acceptance 3.5mm-9mm diameter depending on part code (see data for details)
- Pack of Cable Glands for differing cable sizes also available separately (PX0812)
- Sealing Caps (available separately) can be used to maintain IP rating of unmated connectors:
- PX0811 fits PX0800 Flex Cable Connector
- PX0810 fits all other connectors in the PX08 Mini Series

// General Information:

Product Display Title:

Product Family:

Product Series:

Approvals:

Body Material:

Body Material Type:

Coupling Type:

Diameter Over Coupling Ring Mm:

Flamability Rating:

Function:

Ip Rating:

Max Cable Entry Size:

Min Cable Entry Size:

Max Operating Temperature:

Min Operating Temperature:

Mini Series of modular connectors

Circular Power Connectors

Mini Buccaneer

UL

Polyamide (PA)

Plastic Body

Screw

26mm

UL94V-0

Inline Cable Connector Body

IP68

8mm

6mm

+70°C

-20°C

// Product PDF Links

 Mini Series power connectors...

 Mini Series connectors wiring...