


01 0132

DIN circular connectors



DIN plug with bayonet lock, straight version, shielded,
with metal housing, bend protection and solder terminals

01 0132



Environmental conditions


Temperature range -25 °C/+80 °C

Materials


Insulating body	PA, V-0 according to UL94
Contact pin	CuZn, silver-plated
Strain relief	steel, nickel-plated
Housing	Zn alloy, nickel-plated
Bayonet nut	Zn alloy, nickel-plated
Bend protection sleeve	PVC
Screw	steel, nickel-plated

Pin configurations, solder side view

DIN 41524




0132 03




0132 04

DIN 41524




0132 05

DIN 45322




0132 05-1

DIN 45322




0132 06

DIN 45329



0132 07-1

DIN 45326



0132 08-1

Connectable conductors for solder area

Section	≤ AWG 19 (0.65 mm ²)
Cable diameter	7,0 mm

Electrical data (at T_{amb} 20 °C)

Rated current	4 A
Rated voltage	100 V AC
Rated impulse voltage	250 V AC RMS/60 s
Insulation resistance	≥ 100 MΩ

Associated products

Counterparts

0107

0122

01 0132

Designation	Pole Number	PU (Pieces)	MDQ (Pieces)
0132 03	3	50	150
0132 04	4	50	150
0132 05	5	50	150
0132 05-1	5	50	150
0132 06	6	50	150
0132 07-1	7	50	150
0132 08-1	8	50	150

Packaging:

in individual plastic bags, in a cardboard box