
PX0100S03BK Datasheet



Product Name // 3 Contacts Male Standard Rectangular **Black Connector**

View Product Page





// Product Description:

- 3 Contacts Male Standard Rectangular Black Connector
- 0 Enhanced Seal Protection (ESR), Protective End Cap (PEC), Terminating Resistor (TER), Shrink Boot Adapter (SBA), Welded Flange (WFL) and Y-Type Connector (YTY) Available
- 0 Water and dustproof to IP68 when mated with compatible
- Mate with PX0101 Series, as appropriate

- O Wedgelocks provided
- 0 Crimp Terminals
- 0 Mechanical Cycles = 100 (min)
- 0 Operating Temperature = $-25 \hat{A}^{\circ}C$ to $+120 \hat{A}^{\circ}C$

// General Information:

Product Display Title:

Product Family:

Product Series: Body Colour:

Body Material:

Body Material Type:

Contact Type:

Coupling Type: **Current Max:**

Ip Rating:

Max Operating Temperature: Min Operating Temperature:

Number Of Contacts:

Voltage Max:

3 Contacts Male Standard Rectangular Black Connector

Rectangular Connectors

Standard Rectangular Connectors

Polycarbonate/Polybutylene Terephthalate (PC/PBT)

Plastic Body Socket Contact

Snap-in

13A

IP68

+120°C

-40°C

3 Contacts

250V

// Product PDF Links



Rectangular Connector Datasheet