


EXP-0921/05/S/3 Datasheet

Product Name // Inline Cable Connector EXP-0921 Series 5
Contact Socket 11mm-13mm Cable (Black Gland)

 [View Product Page](#)



// Product Description:	
- Inline Cable Connectors for hazardous areas - Water and dustproof to IP68 when mated with compatible connector - Positive fast-acting locking ring - can be turned with a gloved hand - Plug or Socket 2, 3, 4, 5, 7, 10 Contact with leading Earth on 3, 4, 5, 7 Contact versions, trailing Neutral on 5 Contact version - Screw Terminals	- Choice of cable acceptance 7mm-22mm diameter depending on part code (see data for details): - EXP-09 part codes 7mm-15mm diameter - EXP-A9 part codes (large cable version with strain relief clamp) 14mm-22mm diameter - Packs of Cable Glands for differing cable diameters available separately (EXP-0980, EXP-A980) - EXP-0991 heavy duty Sealing Cap available separately to maintain IP rating of unmated connectors - Mate with EXP-09 or EXP-A9 Series Flex and Panel Mount Connectors, as appropriate

// General Information:	
Product Display Title: Product Family: Product Series: Approvals: Body Material: Body Material Type: Contact Type: Coupling Type: Current Max: Diameter Over Coupling Ring Mm: Flamability Rating: Function: Ip Rating: Max Cable Entry Size: Min Cable Entry Size: Max Contact Accomodation Awg: Min Contact Accomodation Awg: Max Contact Accomodation Mm2: Min Contact Accomodation Mm2: Max Operating Temperature: Min Operating Temperature: Number Of Contacts: Voltage Max:	Inline Cable Connectors for hazardous areas Circular Power Connectors EXPlora UL Polyester (PET) Plastic Body Socket Contact Screw 18A 58mm UL94V-0 Inline Cable Connector IP68 13mm 11mm 14AWG 10AWG 4mm2 2.5mm2 +55°C -20°C 5 Contacts 600V

// Product PDF Links

 [EXPlora Series power connectors...](#)