



**Product:** [BRSCCS 4D/9](#)

M12 Field Attachable, crimp termination, robust metal housing, IP67, male, 4-pin, D-coded, shielded, straight, 250V, 4A

**Product Description**

M12 Field Attachable, crimp termination, robust metal housing, IP67, male, 4-pin, D-coded, shielded, straight, 250V, 4A, suited for rail application acc. to EN 45545, Cat5e

**Technical Specifications**

**Technical Data**

Product Family:	Data Connector
Product Sub Family:	Data Connector
Brand:	Belden
Connector Type:	Field attachable
Type of Contact / Gender:	male
Connector Design:	straight
Number of Pins:	4 (included in the packaging)
Coding:	D
Shielding:	Shielded
Attachment Type:	Coupling Screw
Rated Voltage:	250 V
Rated Impulse Voltage:	2.5kV
Operating Voltage:	50 V AC / 60 V DC
Data Transmission:	Category 5e
Data Transmission Rate:	100 Mbit/s
Contact Resistance:	≤ 10 mOhm
Insulation Resistance:	> 10 <sup>8</sup> Ohm
Mating Cycles:	> 200
Type of Connection:	crimp
Maximum Wire Isolation Diameter:	Ø 6 mm to Ø 8,5 mm
Strain-Relief:	cable gland
Suitable Cables:	gaskets enclosed Ø6 - Ø8.5 mm
Ambient Temperature (Operation)*:	-55 °C to +85 °C, notice derating
Protection Degree / IP Rating**:	IP67
Pollution Degree:	3 acc. to DIN EN 60664-1 (VDE 0110-1)
Clearance / Creepage Distance:	DIN EN 60664-1 (2008/01); VDE 0110-1
Overvoltage Category:	III acc. to DIN EN 60664-1 (VDE 0110-1)

**Materials**

Contact Base Material:	Cu Alloy
Contact Plating:	Cu/Au
Contact Bearer Material:	PA
Contact Bearer Color:	grey
Flammability Class (Contact Bearer):	UL 94 V-0 / F2
Housing Material:	Zamak

Housing Plating:	Ni
Housing Color:	silver
Cable Gland Material:	CuZn
Cable Gland Plating:	Ni
Cable Gland Gasket:	NBR
Strain-Relief Material:	PBT GF
Flammability Class (Strain Relief):	UL 94 V-0 / F2
Attachment Material:	CuZn
Attachment Plating:	Cu/Ni
Shielding Material:	CuZn, plating: Ni

Additional Technical Data

Fastening Torque (Contact Screw):	1.5 -2.0 Nm (max. 3.0Nm), hand-tight
-----------------------------------	--------------------------------------

Safety & Environmental Compliance

RoHS Compliant:	yes, with exeption
-----------------	--------------------

Notes

Note Derating:	* Notice derating
Protection Degree / IP Rating Note:	** only if mounted and locked in combination with Hirschmann / Lumberg Automation connector.

Variants

Item #	Item Description
934885001	BRSCCS 4D/9

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.