

# Product: MPS-8U-RST 4T-2RKT 4T ☑





M12 Power h-splitter: input: male, 4 poles, T-coded; output: 1-2, female, 4 poles, T-coded


# **Product Description**


M12 Power h-splitter: male, straight, 4 poles, T-coded, M12, female, straight, 4 poles, T-coded


### **Technical Drawing**











# **Technical Specifications**

# **Product Description**

Product Family:	Power Connector
Brand:	Lumberg Automation
Connector Type:	Molded Splitter
Rated Voltage:	63 VDC
Rated Current*:	12 A

### **Technical Data Side 1**

M12 Power
male, M12
h shape
Coupling Nut
4
Т
≥10^8 Ohm
100
-30°C to +90°C, notice derating
IEC 61076-2-111
3 acc. to DIN EN 60664-1 (VDE 0110-1)
CuZn
Cu/Au
PA
black
TPU
black
CuZn
Cu/Ni
FPM/FKM

# **Cable Data**

Ambient Temperature (Fixed Installation):	-30°C to +90°C	

# **Technical Data Side 2**

Product Sub Family, Side 2:	M12 Power
Type of Contact / Gender, Side 2:	female, M12
Number of Pins, Side 2:	4
Coding, Side 2:	Т
Contact Base Material, Side 2:	CuZn
Contact Plating, Side 2:	Cu/Au
Contact Bearer Material, Side 2:	PA

Contact Bearer Color, Side 2:	black
Attachment Material, Side 2:	CuZn

### **Technical Data Side 3**

Attachment Material, Side 3:	CuZn
Coding, Side 3:	Т
Contact Base Material, Side 3:	CuZn
Contact Bearer Color, Side 3:	black
Contact Bearer Material, Side 3:	PA
Contact Plating, Side 3:	Cu/Au
Number of Pins, Side 3:	4
Protection Degree / IP Rating (IEC 60529), Side 3:	IP65, IP67, IP68
Rated Current*, Side 3:	12 A
Rated Voltage, Side 3:	63 VDC
Type of Contact / Gender, Side 3:	female, M12

### **Technical Data Side 4**

Product Sub Family, Side 4:	M12 Power
Protection Degree / IP Rating (IEC 60529), Side 4:	IP65, IP67, IP68
Rated Current*, Side 4:	12 A

### **Approvals**

UL-File:	E497237
UL:	cULus

#### Safety & Environmental Compliance

RoHS Compliant:	yes	

### **Notes**

Protection Degree / IP Rating Note:	** only if mounted and locked in combination with Hirschmann / Lumberg Automation connector.
Note Derating:	* Notice derating

#### Variants

Item #	Item Description
935065005	MPS-8U-RST 4T-2RKT 4T

#### © 2024 Belden, Inc

#### All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.