
PXEB5201B450 Datasheet



Product Name // 2 Channel Plug to Plug Connector Cable Assembly







// Product Description:

- 0 Two-terminated Plug Connectors with a 2-Channel OM1 Outdoor Tactical Cable - 450m Long Cable Assembly
- O Designed to MIL-DTL83526D
- 0 Compatible with any connector that follows MIL-DTL83526D
- 0 Dust Cap & Lanyard included for each Connector
- 0 Mates with Plug, Jam Nut, & Flange Mount Connectors (hermaphroditic)
- 0 Operating Temperature -50°C to +80°C
- 0 Available in 4 Channel
- 0 Available in Plug to LC & Plug to SC Cable Assembly

General Information:

Product Display Title: 2 Channel Plug to Plug Connector Cable Assembly

Product Family: Circular Fiber Connectors **Product Series:** 5000 Series Expanded Beam

Max Insertion Loss: <2dB Avg Insertion Loss: <1.5dB **Body Colour:** Dark Grey

Polycarbonate/Polybutylene Terephthalate (PC/PBT) **Body Material:**

Body Material Type: Contact Type: **Expanded Beam** Coupling Type: Screw Diameter Over Coupling Ring Mm: 30mm

OM1 Fibre Mode:

Flamability Rating: UL94V-0 Function: EB Plug to Plug Double Ended Fiber Cable

IP68 Ip Rating:

Material Finish: Max Operating Temperature: Min Operating Temperature: **Rohs Compliant:**

Matt +80°C -50°C Yes

// Product PDF Links

5000 Series Expanded Beam Product.