


RF240EJ Datasheet

Product Name // 2.4mm Jack End Launch RF Connector

 View Product Page



// Product Description:

- 2.4mm Jack End Launch RF Connector
 - Maximum Voltage: 150V
 - Temperature range: -55Â°C to +125Â°C
 - Frecuency range: 0GHz - 50GHz
 - VSWR:
- Dielectric withstanding Voltage: >500V
 - Impedance: 50Ohm
 - Body Material: Stainless Steel Passivation
 - Contact Material: Beryllium Copper

// General Information:

Product Display Title:	2.40mm Series End Launch Connector
Product Family:	Radio Frequency Connectors
Product Series:	2.40mm Series
Body Length:	20.12mm
Body Material:	Stainless Steel Passivation
Centre Contact Retention Force:	>26.7N
Contact Pin Material:	Beryllium Copper
Min Coupling Torque:	0.80Nm
Max Coupling Torque:	1.10Nm
Coupling Nut Retention Force:	>27.2Kg
Dielectric Withstanding Voltage:	>500V
Durability:	>500 cycles
Function:	Female End Launch RF Connector
Impedance:	50Ohm
Insulation Resistance:	>5000MOhm
Insulator:	(UNFILLED ULTEM 1000/PEI) / (Adapter ASTM D 1710)
Max Operating Temperature:	+125°C
Min Operating Temperature:	-55°C
Min Operating Frequency:	0GHz
Max Operating Frequency:	50GHz
Thread Size:	M7x0.5 6g
Voltage Max:	150V
Vswr:	<1.60

// Product PDF Links



Have a question or project enquiry
you'd like to talk to us about?



Click Here To Contact Us