
## **PX0402/009/12S Datasheet**



## Product Name // Right-Angle Overmould Flex Cable Connector PX0402 Series Pre-Wired 9M Cable 12 Contact Socket







## // Product Description:

- Right-Angled Overmoulded Flex Connector pre-wired cable assemblies
- Water and dustproof to IP68 when mated with compatible connector
- O Pin or Socket
- Q 2, 3, 4, 6, 8, 10 or 12 Contact

- Cable acceptance 2.5mm-9mm
- O Choice of cable length depending on part code
- PX0481 Sealing Cap available separately to maintain IP rating of unmated connectors
- Mates with PX0401, PX0411 Inline Connectors and PX0412, PX0413 Panel Mount Connectors

## // General Information:

Product Display Title: Product Family:

Product Series: Approvals:

Body Material: Cable Length: Contact Type: Coupling Type:

Coupling Type: Current Max:

Diameter Over Coupling Ring Mm:

Flamability Rating:

Function: Ip Rating:

Max Operating Temperature: Min Operating Temperature: Number Of Contacts: Voltage Max: Right-Angled Overmoulded Flex Connector pre-wired cable assemblies

Circular Power Connectors 400 Series Buccaneer CSA, UL, VDE Polyurethane (PU)

9m

Socket Contact Screw

1A 19.1mm UL94V-HB

Right Angle Flex Connector Single Ended Cable

IP68, IP69K +85°C -20°C 12 Contacts 50V

