

PXF6055AAA Datasheet

Product Name // 05 M, OM3 Multi Mode, Cabled, Flex fiber connector

 [View Product Page](#)



// Product Description:	
 Flex Fiber Connector to Flex Fiber Connector	 Choices of OS1, OM1 and OM3 cables for single or multimode
 Sealed to IP66, IP68, IP69K when mated with compatible connector	 PXP6083 Sealing Cap available separately to maintain IP rating of unmated connectors
 no cable options, or pre-terminated from 5M - 450M available	 Mate with Inline fiber connector or panel mount connectors PXF6051, PXF6052
 Duplex LC type fiber connector	

// General Information:	
Product Display Title:	Flex Fiber Connector to Flex Fiber Connector
Product Family:	Circular Fiber Connectors
Product Series:	6000 Series - Duplex LC Fiber Buccaneer
Body Material:	Polyamide (PA)
Contact Type:	LC Fiber
Coupling Type:	30 Degree coupling
Diameter Over Coupling Ring Mm:	32mm
Fibre Mode:	OM3
Flamability Rating:	UL94V-0
Function:	Flex to LC Connector Double Ended Fiber Cable
Ip Rating:	IP66, IP68, IP69K
Max Operating Temperature:	+70°C
Min Operating Temperature:	-25°C

// Product PDF Links

 6000 Series Fiber connectors...