


PX0402/008/2S Datasheet

 [View Product Page](#)

Product Name // Right-Angle Overmould Flex Cable
Connector PX0402 Series Pre-Wired 8M Cable 2 Contact
Socket



// **Product Description:**

- Right-Angled Overmoulded Flex Connector pre-wired cable assemblies
 - Water and dustproof to IP68 when mated with compatible connector
 - Pin or Socket
 - 2, 3, 4, 6, 8, 10 or 12 Contact
- Cable acceptance 2.5mm-9mm
 - Choice of cable length depending on part code
 - PX0481 Sealing Cap available separately to maintain IP rating of unmated connectors
 - Mates with PX0401, PX0411 Inline Connectors and PX0412, PX0413 Panel Mount Connectors

// **General Information:**

Product Display Title:	Right-Angled Overmoulded Flex Connector pre-wired cable assemblies
Product Family:	Circular Power Connectors
Product Series:	400 Series Buccaneer
Approvals:	CSA, UL, VDE
Body Material:	Polyurethane (PU)
Cable Length:	8m
Contact Type:	Socket Contact
Coupling Type:	Screw
Current Max:	8A
Diameter Over Coupling Ring Mm:	19.1mm
Flamability Rating:	UL94V-HB
Function:	Right Angle Flex Connector Single Ended Cable
Ip Rating:	IP68, IP69K
Max Operating Temperature:	+85°C
Min Operating Temperature:	-20°C
Number Of Contacts:	2 Contacts
Voltage Max:	250V

// **Product PDF Links**

