





**Product:** [RSMED 3](#)

M8 Insert Sensor/Actuator Receptacle Connector: Male, insert with light indicator windows, M8 - mating side, solder contacts - connecting side, 3-pin, A-coded, unshielded, metallic grey housing, 50 AC / 60 DC, 4 A (24 AWG)

## Product Description

M8 Insert Sensor/Actuator Receptacle Connector: Male, insert with light indicator windows, M8 - mating side, solder contacts - connecting side, 3-pin, A-coded, unshielded, metallic grey housing, 50 AC / 60 DC, 4 A (24 AWG)

## Technical Drawing



## Technical Specifications

### Technical Data

|                           |                                     |
|---------------------------|-------------------------------------|
| Product Family:           | Sensor / Actuator Connectors        |
| Product Sub Family:       | M8 Insert                           |
| Mating Side:              | M8                                  |
| Connecting Side:          | Solder Contacts                     |
| Brand:                    | Lumberg Automation                  |
| Connector Type:           | Receptacle                          |
| Type of Contact / Gender: | Male                                |
| Connector Design:         | Insert with Light Indicator Windows |
| Number of Pins:           | 3                                   |
| Coding:                   | A                                   |
| Shielding:                | Unshielded                          |
| Attachment Type:          | Snap- and Screw-Locking             |
| Rated Voltage:            | 60 V                                |
| Rated Voltage (UL):       | 30 V AC/DC                          |
| Rated Impulse Voltage:    | 1.5 kV                              |
| Operating Voltage:        | 50 AC / 60 DC                       |
| Rated Current*:           | 4 A (24 AWG)                        |
| Rated Current (UL)*:      | 4 A                                 |
| Contact Resistance:       | ≤ 10 mOhm                           |

|                                   |                                         |
|-----------------------------------|-----------------------------------------|
| Insulation Resistance:            | > 10^9 Ohm                              |
| Mating Cycles:                    | ≤ 100                                   |
| Type of Connection:               | Solder                                  |
| Ambient Temperature (Operation)*: | - 25 °C - + 90 °C                       |
| Operating Temperature (UL):       | max. + 75 °C                            |
| Protection Degree / IP Rating**:  | IP65, IP67                              |
| Design Standard:                  | IEC 61076-2-104                         |
| Pollution Degree:                 | 3 acc. to DIN EN 60664-1 (VDE 0110-1)   |
| Overvoltage Category:             | III acc. to DIN EN 60664-1 (VDE 0110-1) |

Materials

|                                      |             |
|--------------------------------------|-------------|
| Contact Base Material:               | CuZn        |
| Contact Plating:                     | Cu/Au       |
| Contact Bearer Material:             | PA          |
| Contact Bearer Color:                | Transparent |
| Flammability Class (Contact Bearer): | UL 94 V-2   |
| Potted:                              | No          |
| Housing Material:                    | CuZn        |
| Housing Plating:                     | Cu/Ni       |
| Housing Color:                       | Silver      |
| Attachment Material:                 | CuZn        |
| Attachment Plating:                  | Cu/Ni       |

Additional Technical Data

|                                |                           |
|--------------------------------|---------------------------|
| Fastening Torque (Attachment): | M 8x1: 30 Ncm, hand-tight |
|--------------------------------|---------------------------|

Approvals

|          |             |
|----------|-------------|
| UL-File: | E104696     |
| UL:      | UL 2238; UR |

Safety & Environmental Compliance

|                 |     |
|-----------------|-----|
| RoHS Compliant: | yes |
|-----------------|-----|

Notes

|                                     |                                                                                                                                                                  |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Note Derating:                      | * Notice derating                                                                                                                                                |
| Protection Degree / IP Rating Note: | * only if mounted and locked in combination with Hirschmann / Lumberg connector. On the installation side tightness has to be assured by taking proper measures. |

Variants

| Item # | Item Description |
|--------|------------------|
| 11657  | RSMED 3          |

© 2024 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.