



Product: <u>70007E</u> ☑

DataTuff® 5E, 1Q #22 Str TC, PO ins, F/B, PVC jkt, PROFINET Type B

Product Description

DataTuff® 5E, 1 Quad AWG 22 Tinned Copper - Stranded, Polyethylene insulation, SF/UTP - Overall Braid + Foil shielding, PVC jacket , PROFINET Type B

Technical Specifications

Product Overview

Suitable Applications: PROFINET Cat5e, harsh environment, IIoT, factory or process automation, IP cameras and devices, data communication, etc.

Construction Details

Conductor

| Size | Stranding | Material | No. of Pairs | No. of Elements |
|--------|-----------|--------------------|--------------|-----------------|
| 22 AWG | 7x0.25 mm | TC - Tinned Copper | 2 | 4 |

Insulation

| Material | Nom. Insulation Diameter | Color Code |
|-------------------|--------------------------|--------------------------------|
| PE - Polyethylene | 1.55 mm (0.0610 in) | White & Blue & Yellow & Orange |
| | | 1 Quad |

Cable Core

Description

1 quad with center filler

Inner Jacket

| Material | | Nom. Diameter |
|---|---------|------------------|
| LSZH - Low Smoke Zero Halogen (Flame Retardant) | | 4.1 mm (0.16 in) |
| Table Notes: | Bedding | |

Outer Shield

| Shield Type | Material | Coverage |
|-------------|-------------------------|----------|
| Таре | Bi-Laminate (Alum+Poly) | |
| Braid | Tinned Copper (TC) | 85% |

Outer Jacket

| | Material Nor | n. Diameter |
|---|--------------------------------|--------------|
| | PVC - Polyvinyl Chloride 6.5 i | mm (0.26 in) |
| C | Overall Cable Diameter (Nomin | nal): 6.5 mm |

Electrical Characteristics

Electricals

| | | Nom. Characteristic Impedance | |
|--|-------------|-------------------------------|--|
| | 57.1 Ohm/km | 100 Ohm | |

Delay

| Max. Delay | Nom. Velocity of Prop. | |
|-------------|------------------------|--|
| 530 ns/100m | 68% | |

High Frequency

| Frequency [MHz] | Max. Insertion Loss (Attenuation) | Min. NEXT [dB] | Min. ACRF (ELFEXT) [dB] | Min. SRL (Structural Return Loss) [dB] |
|-----------------|-----------------------------------|----------------|-------------------------|--|
| 1 | 2.1 dB/100m | 65.3 | 64 | |
| 4 | 4.1 dB/100m | 56.3 | 52 | 23 |
| 10 | 6.5 dB/100m | 50.3 | 44 | 25 |
| 16 | 8.3 dB/100m | 47.2 | 40 | 25 |
| 31.25 | 11.7 dB/100m | 42.9 | 34 | 23.6 |
| 62.5 | 17 dB/100m | 38.4 | 28 | 21.5 |
| 100 | 22 dB/100m | 35.3 | 24 | 20.1 |

Reference standard: ISO/IEC 11801 ed 2.0, Cat 5e

Transfer Impedance

Table Notes:

| Frequency | Max. Transfer Impedance | | |
|-----------|-------------------------|--|--|
| 10 Mhz | Max. 10 mOhm/m | | |

Voltage

Voltage Rating 300 V

Mechanical Characteristics

Temperature

| Operating | Installation | Storage |
|----------------|---------------|----------------|
| -40°C to +80°C | -5°C To +60°C | -40°C to +80°C |

Standards and Compliance

| Environmental Suitability: | Indoor - Euroclass Eca, Sunlight Resistance - Black only, Oil Resistance |
|----------------------------------|--|
| Flammability / Reaction to Fire: | IEC 60332-1-2 |
| CPR Compliance: | CPR Euroclass: Eca; CPR UKCA Class: Eca |
| AWM Compliance: | AWM 2464 |
| Data Category: | Category 5e |
| ISO/IEC Compliance: | ISO/IEC 11801-1 |
| European Directive Compliance: | EU CE Mark |
| UK Regulation Compliance: | UKCA Mark |

History

| Update and Revision: | Revision Number: 0.266 Revision Date: 04-29-2024 |
|----------------------|--|
| | |

Part Numbers

Variants

| Item # | Color | Putup Type | Length | EAN |
|---------------|-------|------------|---------|---------------|
| 70007E.01B100 | Green | Flat Box | 100 m | 8719605009333 |
| 70007E.01305 | Green | Reel | 305 m | 8719605009319 |
| 70007E.01500 | Green | Reel | 500 m | 8719605009326 |
| 70007E.011000 | Green | Reel | 1,000 m | 8719605009296 |
| 70007E.011525 | Green | Reel | 1,525 m | 8719605009302 |

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.