


# PXEB5202C450 Datasheet

Product Name // 2 Channel Plug to LC Connector Cable Assembly

 [View Product Page](#)



// Product Description:

- A Terminated Plug Connector with a 2-Channel OM3 Outdoor Tactical Cable that breaks out in 2 independent cables (0.5m long) with LC Terminations - 450m Long Cable Assembly
  - Designed to MIL-DTL83526D
  - Compatible with any connector that follows MIL-DTL83526D
  - Dust Cap for all Connectors & Plug Lanyard Included
- Mates with Plug, Jam Nut, & Flange Mount Connectors (hermaphroditic)
  - Operating Temperature -50Â°C to +80Â°C
  - Available in 4 Channel
  - Available in Plug to Plug & Plug to SC Cable Assembly

// General Information:

|                                 |                                                   |
|---------------------------------|---------------------------------------------------|
| Product Display Title:          | 2 Channel Plug to LC Connector Cable Assembly     |
| Product Family:                 | Circular Fiber Connectors                         |
| Product Series:                 | 5000 Series Expanded Beam                         |
| Max Insertion Loss:             | <2dB                                              |
| Avg Insertion Loss:             | <1.5dB                                            |
| Body Colour:                    | Dark Grey                                         |
| Body Material:                  | Polycarbonate/Polybutylene Terephthalate (PC/PBT) |
| Body Material Type:             | Plastic Body                                      |
| Contact Type:                   | Expanded Beam                                     |
| Coupling Type:                  | Screw                                             |
| Diameter Over Coupling Ring Mm: | 30mm                                              |
| Fibre Mode:                     | OM3                                               |
| Flamability Rating:             | UL94V-0                                           |
| Function:                       | EB Plug to LC Double Ended Fiber Cable            |
| Ip Rating:                      | IP68                                              |
| Material Finish:                | Matt                                              |
| Max Operating Temperature:      | +80°C                                             |
| Min Operating Temperature:      | -50°C                                             |
| Rohs Compliant:                 | Yes                                               |

// Product PDF Links

