


Product Name // SMA Straight Jack RF Connector, Bulkhead

 [View Product Page](#)

* Representative product image only





// Product Description:	
 SMA Straight Jack RF Connector, Bulkhead	 Dielectric withstanding Voltage: >750V
 Maximum Voltage: 335V	 Impedance: 50Ohm
 Temperature range: -65Â°C to +165Â°C	 Body Material: Stainless Steel Passivation
 Frecuency range: 0GHz - 26.5GHz	 Contact Material: Beryllium Copper
 VSWR:	

// General Information:	
Product Display Title:	SMA Series Bulkhead
Product Family:	Radio Frequency Connectors
Product Series:	SMA Series
Body Length:	10.80mm
Body Material:	Stainless Steel Passivation
Centre Contact Retention Force:	>26.7N
Contact Pin Material:	Beryllium Copper
Min Coupling Torque:	0.80Nm
Max Coupling Torque:	1.10Nm
Coupling Nut Retention Force:	>27.2Kg
Dielectric Withstanding Voltage:	>750V
Durability:	>500 cycles
Function:	Female RF Bulkhead
Impedance:	50Ohm
Insulation Resistance:	>5000MOhm
Insulator:	Adapter ASTM D 1710
Max Operating Temperature:	+165°C
Min Operating Temperature:	-65°C
Min Operating Frequency:	0GHz
Max Operating Frequency:	26.5GHz
Socket Diameter:	0.30mm
Socket Outer Diameter:	1.94mm
Thread Size:	1/4 36UNS 2A
Voltage Max:	335V
Vswr:	<1.30

// Product PDF Links

 [SMA Series Product Datasheet](#)