

Tools and harnessing machines



Semiautomatic harnessing machine for termination of RAST 2.5 connectors in insulation displacement technology (IDT), larger base machine, with integrated stations for removal of connector chain interlinks and cable color detection, individual upgrading possible

Approvals: (6

1 of 4 07/2024

Range of application

351..., 351...-2, 351...-4, 352..., 352...-2 Connector

Pole number 2-20 2.5/5.0 mm State of delivery of connectors in chain

discrete conductor, pre-notched ribbon cable* 2.5/5.0 mm Processable conductor

Features

middle and high-volume Application

production

Stroke capacity ca. 1200/h

- Automatic feeding of connectors Scope of functions and delivery

- Cable screen for one range of cable diameters/sections - Verification of insertion pattern and line end position during manual

insertion of conductors - Fixation of inserted discrete conductors by spring-loaded pressure pads

until pressing

- Automatic release of press action by control of line end position - Cutting station for connector chain interlinks (station RK) Cable color detection 7 + 1

(station CA)

Vacuum extraction device for removal of cut connector chain interlinks

Storage of insertion patterns - Harnessing of bus cables not

Options - Special press die, required for 351... with side **P2** being closed

- Special press die, required for 3517-5 (for 1 mm printed circuit

board)

- Cable screens for additional ranges of cable diameters/sections *Conversion kit for ribbon cable (cable screen, holder, test pins,

support)

- Set of test pins for 35...-2 (20

pieces)

Dimensions and supply data

Dimensions (H x W x D) 590 mm x 1320 mm x 870 mm

Weight ca. 125 kg Electrical supply 230 V/50 Hz Compressed air supply 6 bar

Compressed air consumption 4,5 m³/1000 connectors

2 of 4 07/2024



Associated products

Accessories ☑ HZ35-V

3 of 4 07/2024



Designation	Pole Number	PU (Pieces)	MDQ (Pieces)
HA35f-RK-CA			

4 of 4 07/2024