



Product: [74005PU](#)

DataTuff® 7, 4PR #26 Str BC, PO ins, S/FTP, PUR HF jkt, AWM 21292

Product Description

DataTuff® 7, 4 Pair AWG 26 Bare Copper - Stranded, Polyethylene insulation, S/FTP - Overall Braid / Individual Foil shielding, PUR Halogen Free jacket , AWM 21292

Technical Specifications

Product Overview

| | |
|------------------------|--|
| Suitable Applications: | Cat7, harsh environment, IIoT, factory or process automation, video, audio, data communication, etc. |
|------------------------|--|

Construction Details

Conductor

| Size | Stranding | Material | No. of Pairs | No. of Elements |
|--------|-----------|------------------|--------------|-----------------|
| 26 AWG | 7x0.16 mm | BC - Bare Copper | 4 | 8 |

Insulation

| Material | Nom. Insulation Diameter | Color Code |
|--------------------------|--------------------------|--|
| PE - Polyethylene (Foam) | 1.05 mm (0.0413 in) | White/Blue & Blue, White/Orange & Orange, White/Green & Green, White/Brown & Brown |

Cable Core

| Description |
|-------------------------------|
| 4 pairs twisted to cable core |

Inner Shield

| Element | Shield Type | Material |
|--------------------------|-------------|-------------------------|
| Individual Shielded Pair | Tape | Bi-Laminate (Alum+Poly) |

| | |
|--------------|------------------|
| Table Notes: | Aluminum outside |
|--------------|------------------|

Outer Shield

| Shield Type | Material | Coverage |
|-------------|--------------------|----------|
| Braid | Tinned Copper (TC) | 65% |

Outer Jacket

| Material | Nom. Diameter |
|-----------------------------------|------------------|
| PUR - Polyurethane (Halogen Free) | 6.8 mm (0.27 in) |

| | |
|-----------------------------------|------------------------|
| Table Notes: | Flame Retardant Sheath |
| Overall Cable Diameter (Nominal): | 6.8 mm (0.27 in) |

Electrical Characteristics

Electricals

| Max. Conductor DCR | Max. Mutual Capacitance | Max. Capacitance Unbalance | Nom. Characteristic Impedance |
|--------------------|-------------------------|----------------------------|-------------------------------|
| 145 Ohm/km | 56 pF/m (17 pF/ft) | 160 pF/100m | 100 Ohm |

Delay

| Max. Delay Skew | Nom. Velocity of Prop. |
|-----------------|------------------------|
| 40 ns/100m | 70% |

High Frequency

| Frequency [MHz] | Max. Insertion Loss (Attenuation) | Min. NEXT [dB] | Min. PSNEXT [dB] | Min. ACRF (ELFEXT) [dB] | Min. PSACRF (PSELFEXT) [dB] | Min. RL (Return Loss) [dB] |
|-----------------|-----------------------------------|----------------|------------------|-------------------------|-----------------------------|----------------------------|
| 1 | 2.7 dB/100m | 80 | 77 | | | |
| 4 | 5.5 dB/100m | 80 | 77 | 58 | 55 | 23 |
| 10 | 8.5 dB/100m | 80 | 77 | 50 | 47 | 25 |
| 16 | 10.8 dB/100m | 80 | 77 | 46 | 43 | 25 |
| 20 | 12.1 dB/100m | 80 | 77 | 44 | 41 | 25 |
| 31.25 | 15.2 dB/100m | 80 | 77 | 40 | 37 | 23.6 |
| 62.5 | 21.8 dB/100m | 75.1 | 72.1 | 34 | 31 | 21.5 |
| 100 | 27.8 dB/100m | 72.4 | 69.4 | 30 | 27 | 20.1 |
| 200 | 40.1 dB/100m | 67.9 | 64.9 | 24 | 21 | 18 |
| 300 | 50 dB/100m | 65.3 | 62.3 | 20 | 17 | 17.3 |
| 600 | 73.3 dB/100m | 60.8 | 57.8 | 14 | 11 | 17.3 |

Transfer Impedance

| Frequency | Max. Transfer Impedance |
|-----------|-------------------------|
| 10 Mhz | Max. 5 mOhm/m |

Voltage

| UL Voltage Rating | Voltage Rating |
|-------------------|-----------------------|
| 30 V RMS | 450 V DC and 300 V AC |

Mechanical Characteristics

Temperature

| Operating | Installation | Storage |
|----------------|----------------|----------------|
| -40°C to +80°C | -15°C To +60°C | -40°C to +80°C |

Bend Radius

| Stationary Min. | Installation Min. |
|-----------------|-------------------|
| 30 mm (1.2 in) | 65 mm |

| | |
|--------------------|---------------|
| Max. Pull Tension: | 80 N (18 lbf) |
|--------------------|---------------|

Standards and Compliance

| | |
|----------------------------------|--|
| Environmental Suitability: | Indoor/Outdoor, Indoor, Sunlight Resistance, Oil Resistance |
| Flammability / Reaction to Fire: | IEC 60332-1-2 |
| AWM Compliance: | AWM 21292 |
| Data Category: | Category 7 |
| TIA/EIA Compliance: | ANSI/TIA 568.2-D |
| ISO/IEC Compliance: | ISO/IEC 11801-1 |
| CENELEC Compliance: | EN 50173-1 |
| European Halogen Free Standards: | IEC 60754-1 - Halogen Amount = Zero, IEC 60754-2 - Halogen Acid Gas Amount - Max. Conductivity = 10 µS/mm, IEC 60754-2 - Halogen Acid Gas Amount - Min. pH = 4.3 |
| European Directive Compliance: | EU CE Mark |

History

| | |
|----------------------|--|
| Update and Revision: | Revision Number: 0.268 Revision Date: 05-27-2024 |
|----------------------|--|

Part Numbers

Variants

| Item # | Color | Putup Type | Length | EAN |
|----------------|-------------|------------|--------|---------------|
| 74005PU.02B100 | Black | Flat Box | 100 m | 8719605013361 |
| 74005PU.02305 | Black | Reel | 305 m | 8719605013347 |
| 74005PU.02500 | Black | Reel | 500 m | 8719605013354 |
| 74005PU.01500 | Blue, Water | Reel | 500 m | 8719605013330 |

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.